

KLS

Sealless Steel Strapping Head

Simple, durable, all electric

No adjustments or settings are necessary.



Sealless joint

The KLS forms a sealless joint, eliminating the cost of metal seals.

Easy to operate and maintain

The KLS's modular design offers fast, easy maintenance. The sealing module and tension wheel can be removed in 5 minutes, ensuring quick changeover and minimal downtime.

Made in the U.S.A.

Specifications:

For use on 1/2", 5/8" and 3/4"
(12.7mm, 15.9mm and 19.0mm)
Apex Plus™ and Magnus® steel
strapping in gauges up to .031"
(0.79mm).

Tension: Up to 1600 lbs. (7 000 N)

Electrical: 230/460 volts, 3 phase,
60 Hz standard; 208/415 volts,
3 phase, 50 Hz optional

Weight: 253 lbs. (114.8 kg)

The KLS sealless steel strapping head is designed for 1/2", 5/8" and 3/4" (12.7mm, 15.9mm and 19.0mm) Apex Plus™ and Magnus® steel strapping in gauges up to .031" (0.79mm). This versatile strapping head is designed for medium to heavy-duty applications in a wide range of industries, including metals and lumber. Three versions of the sealing mechanism are available to form a 2-punch key joint, 3-punch key joint or a 4-punch key joint, with one reverse locking key.

SIGNODE INDUSTRIAL GROUP
3610 West Lake Avenue
Glenview, Illinois 60025