

# TableTyer

Plastic strapping machine

Economical • Easy to operate • Reliable



 **SIGNODE®**

# TableTyer

## Plastic strapping machine

### Simple operation

The TableTyer is easy to set up and operate:


1. Select the strap length and tension on the control panel



2. Place strap around the package, and re-insert the strap end into the machine. The TableTyer automatically removes the slack by pulling the desired tension and joins the strap ends with a secure heat weld. The system automatically feeds another length of strap for the next package or bundle.

### Low maintenance with reliable operation

Built with few wearing parts, the TableTyer requires very little maintenance. The 24 VDC motor runs only when the machine is cycling. The heater is "stepped down" to 24 VAC to prolong the life of the heat knife. The sensor controlled heat sealing mechanism ensures consistent, high-efficiency seals. Weld cooling time can be adjusted for proper sealing.



### Precise strap placement

The package stop helps ensure tight, straight strap application.



### Flexible design

The TableTyer features a flexible design for varying applications. Strapping guides are adjustable for strap sizes from 1/4" to 1/2". The tabletop height is adjustable for integration into varying production lines.

### Compact footprint

The TableTyer's internal strapping dispenser helps to conserve floor space.



### TableTyer Specifications

#### Package size:

Minimum: 2" H x 3-1/2" W (50.8 mm x 88.9 mm)  
Maximum: Unlimited

**Strapping:** Empax 1/4", 3/8", or 1/2" plastic strapping

**Strap tension:** 2-100 lbs.

**Electrical requirements:** 120 Volts, Single Phase, 60Hz

**Machine weight:** 168 lbs.

**SIGNODE INDUSTRIAL GROUP**  
3640 West Lake Avenue  
Glenview, IL 60026  
1-800-323-2464 | [www.signode.com](http://www.signode.com)

©2015 SIGNODE SPD1469 01-29-15