


# 4RM



## 4RM Case sealer for random cartons

### Productivity Focus

Performance operating speed of 20 meters per minute

### Easy Maintenance

Easy access to motors, electrical components and belts for maintenance

### Production Versatility

Wide range of supported case sizes to meet customer requirements

### Operator Friendly

Easy to operate with simple controls and intuitive tape roll replacement

# 4RM

## Case sealer for random cartons



### Features and Benefits

- Automatic sealing of random size cartons
- Machine automatically adjusts to varying size cartons
- Suited for random sealing of tall and heavy cartons
- Independently controlled top and bottom drives for smooth flow of heavy cartons
- Ideal for integrating with different production lines
- Auto On/Off enables power saving during idle time
- Twin mast column for greater stability during operation
- Uniform and controlled pressure during taping



### Utility Requirements

|                    |                          |
|--------------------|--------------------------|
| <b>Power</b>       | 415 VAC, 3 Phase, 50 Hz  |
| <b>Consumption</b> | 0.4 KW                   |
| <b>Pneumatic</b>   | 6 Bar - 9.5 Liters/Cycle |

### Case Dimensions

|                   |                    |
|-------------------|--------------------|
| <b>Length</b>     | 150mm to Unlimited |
| <b>Width</b>      | 160mm to 450mm     |
| <b>Height</b>     | 100mm to 400mm     |
| <b>Weight</b>     | 2 to 15 Kg         |
| <b>Carton Ply</b> | Minimum 3 Ply      |

### Technical Specifications

|                         |                           |
|-------------------------|---------------------------|
| <b>Tape Head</b>        | Standard (2", 2.5", 3")   |
| <b>Tape Roll Length</b> | 65 M / 650 M / 1000 M     |
| <b>Machine Length</b>   | 1080mm                    |
| <b>Machine Width</b>    | 570mm                     |
| <b>Machine Height</b>   | 1385mm                    |
| <b>Weight</b>           | 159 Kg                    |
| <b>Drive Motor</b>      | 0.25 HP, 2 No.            |
| <b>Belt Speed</b>       | 20 m / minute             |
| <b>Throughput</b>       | Up to 16 cartons / minute |

### Available Options

- No/Low tape indicator reduces changeover downtime
- Polycarbonate machine guards for operator protection